

 MULTICARGO				
Model	eONE flatbed	eONE tipper	eONE box	eFEST van
Cabin	2 seats	2 seats	2 seats	2 seats
Wheelbase (mm)	2630	2630	2630	3050
Dimensions (mm)	3820*1490*1680	3820*1490*1680	3820*1490*1925	4525*1610*1900
Cargo space size (mm)	2015*1400*320	2015*1400*320	2045*1420*1195	2668*1457*1340
Cargo space volume (m ³)	/	/	3,47 m ³	5,2 m ³
Payload kg	850	850	790	1045 kg
Curb weight kg	850	850	910	1465 kg
Gross vehicle weight kg	1700	1700	1700	2510 kg
Tire size	145/R12 LT	145/R12 LT	145/R12 LT	175/70R14C
Brake system	Front disc / rear drum	Front disc / rear drum	Front disc / rear drum	Front disc / rear drum
Front axle	MacPherson	MacPherson	MacPherson	MacPherson
Rear axle	Leaf springs	Leaf springs	Leaf springs	Multi-link
Transmission	Automat	Automat	Automat	Automat
On-board battery	12V	12V	12V	12V
Traction battery (KWh)	15,40	15,40	15,40	41,86
	23,50	23,50	23,50	
Battery type	LFP	LFP	LFP	LFP / CATL
Voltage architecture	/	/	/	400 V
Basic warranty	2 years – 80,000 km	2 years – 80,000 km	2 years – 80,000 km	4 years - 80,000 km
Battery & motor warranty	5 years – 120,000 km	5 years – 120,000 km	5 years – 120,000 km	5 years - 160,000 km
Motor	Synchronous with permanent magnet	Synchronous with permanent magnet	Synchronous with permanent magnet	Synchronous with permanent magnet
AC charging	2,2 kW	2,2 kW	2,2 kW	3,6 kW
DC charging	/	/	/	50 kW
Connector type	Type 2	Type 2	Type 2	Type 2 / CCS2
Charging time 10–80%	4 hours	4 hours	4 hours	40 minutes
Rated motor power	15 kW	15 kW	15 kW	30 kW
Peak motor power	30 kW	30 kW	30 kW	60 kW
Torque (N·m)	110 N·m	110 N·m	110 N·m	220 N·m
Max speed (km/h)	73	73	73	100
Drive type	rear	rear	rear	rear
City range**	150 / 220	150 / 220	150 / 220	300 km
Combined range**	120 / 180	120 / 180	120 / 180	250 km
Equipment				
ABS + EBD	●	●	●	●
Power steering	●	●	●	●
Infotainment	BT	BT	BT	Radio
Cabin air conditioning	●	●	●	●
Heating	●	●	●	●
Electric windows	●	●	●	●
USB	●	●	●	●
Parking camera	●	●	●	/
Parking sensors	/	/	/	●
Central locking	●	●	●	●
www.multicargo-ev.com info@multicargo-ev.com				

** The stated vehicle range was measured under ideal conditions — at a temperature of 25 °C, no wind, and without load. The actual range may vary depending on the cargo weight, driving style, weather conditions, and route profile.